

2-Lines Entry-level IP Phone

FAP2710P / FAP2710G

FIBERME FAP2710P / FAP2710G is a cost-effective SIP phone with multi-function. It features a 2.3-inch 128x48 pixel dot-matrix display, supporting 2 SIP lines and local 6-party conferencing to render a user-friendly experience. FAP2710P/ FAP2710G has rich functions such as HD audio, dual 10/100Mbps network ports, dual 1Gbps network ports, and integrated PoE, providing an efficient and high-quality business communication experience for enterprises.

Model	Network	PoE	PSU Included
FAP2710P	Dual Ethernet 100Mbps	Yes	No
FAP2710G	Dual Ethernet 1Gbps	Yes	No



Main Functions

- Local Phonebook (1000 entries)
- Call logs (In/Out/Missed, 600 entries)
- Blocked List/Allowed List
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forward (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (With server)
- 6-party Conference
- Hot Line
- Hot desking



Full-duplex speakerphone with HD audio to maximize audio quality and clarity



PoE

FAP2710P / FAP2710G includes built-in PoE to power the device and give it a network connection



Supports 6-way audio conferencing for easy conference calls



2.3" 128 x 48px Graphic LCD screen with backlight with an adjustable backlight



Supports 2 SIP accounts



Electronic Hook Switch (EHS) support for Plantronics, Jabra, and Sennheiser headsets

- 2.3-inch 128x48 pixel dot-matrix display
- Support audio codec G.722 and Opus, HD audio on speakerphone and handset
- Support 6-party local conference
- Support EHS wireless headset
- Dual network ports, integrated PoE
- Two installation methods of desktop stand and wall mountable

LCD Screen	2.3" 128 x 48-pixel graphical LCD with Backlight
Function Keys	<ul style="list-style-type: none"> • 9 Function keys (Hold/Transfer/Voice message/Conference/Phonebook /MWI/Headset/Redial/Hands-free) • 4 Soft keys, 4 navigate keys, volume+/-
SIP Accounts	2 SIP accounts
Ethernet Ports	<ul style="list-style-type: none"> • 2x 100Mbps • 2x 1Gbps (FAP2710G only) • Support PoE
Other Ports	1 x Handset port, 1 x RJ9 Headset port
Direct IP Call	Supported
Phonebook	1000 records; phonebook search/import/export; XML/LDAP remote phonebook; blacklist
Call History	600 records; call history: all/missed/dialed/received
Audio Conferencing	Supports 6-way audio conferencing for easy conference calls
Network Safety	<ul style="list-style-type: none"> • Physical: Ethernet, dual bridged port for PC bypass • IP Mode: IPv4/IPv6 • IP Configuration: Static IP / DHCP / PPPoE • Network Access Control: 802.1x • VPN: L2TP / OpenVPN • VLAN • LLDP • QoS • RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035)
Auto-provision	Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
Audio Codec	<ul style="list-style-type: none"> • Narrowband Codec: G.711a/u, G.723.1, G.726, G.729A/B, iLBC/Opus • Wideband Codec: G.722, Opus
Power	<ul style="list-style-type: none"> • DC Power Input: 5V/0.6A • Power Consumption(Adapter): 0.8~1.29W • Power Consumption(PoE): 1.25~1.86W



FIBERME Communications LLC
1749 Old Meadow Rd., Suite 401
McLean, VA 22102, USA



www.fiberme.com
sales@fiberme.com

