

FAP2730 (P) / (G) / (W)

IP Phone

4-Lines Mid-Level IP Phone

FAP2730P / FAP2730G / FAP2730W

FIBERME FAP2730P / FAP2730G / FAP2730W is a costeffective color screen SIP phone with high performance, especially for enterprises. It features a 2.4-inch 320x240 pixel color screen, supporting 4 SIP lines and local 6-party conferencing to render a user-friendly experience. FAP2730 Series has rich functions such as HD audio, dual 100Mbps network ports, dual 1Gbps network ports (FAP2730G), and integrated PoE, Wi-Fi 2.4GHz / 5GHz (FAP2730W) providing an efficient and high-quality business communication experience for enterprises.

Model	Network	PoE	Wi Fi	PSU Included
FAP2730P	Dual Ethernet 100Mbps	Yes		No
FAP2730G	Dual Ethernet 1Gbps	Yes		No
FAP2730W	Dual Ethernet 100Mbps	Yes	Yes	Yes



Main Functions

- Local Phonebook (1000 entries)
- Call logs (In/Out/Missed, 600 entries)
- Blocked List/Allowed List
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Call out / Answer / Reject
- Mute / Unmute (Microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forward (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (Depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (With server)
- 6-party Conference
- Hot Line
- Hot desking



Full-duplex speakerphone with HD audio to maximize audio quality and clarity



Supports 6-way audio conferencing for easy conference calls

Supports 4 SIP accounts

- 2.4-inch 320x240 pixel color display
- Support audio codec G.722 and Opus, HD audio on speakerphone and handset
- Support 6-party local conference
- Support EHS wireless headset
- Dual network ports, integrated PoE
- Two installation methods of desktop stand and wall • mountable



FAP2730 Series includes built-in PoE to power the device and give it a network connection

2.4" 320 x 240px Graphic Color screen with backlight with an adjustable backlight



Electronic Hook Switch (EHS) support for Plantronics, Jabra, and Sennheiser headsets



FAP2730 (P) / (G) / (W) IP Phone

LCD Screen	2.4-inch 320x240 pixel color screen	
Function Keys	 9 Function keys (Hold/Transfer/Voice message/Conference/Phonebook /MWI/Headset/Redial/Hands-free) 3 Line keys (With LED Indicator Light) 4 Soft keys, 4 navigate keys, volume+/- 	
SIP Accounts	4 SIP accounts	
Network	 2x Ethernet Ports 100Mbps (FAP2730P / FAP2730W) 2x Ethernet Ports 1Gb (FAP2730G only) Wi-Fi 2.4GHz / 5GHz (FAP2730W) Support PoE 	
Other Ports	1 x Handset port, 1 x RJ9 Headset port	
Direct IP Call	Supported	
Phonebook	1000 records; phonebook search/import/export; XML/LDAP remote phonebook; blacklist	
Call History	600 records; call history: all/missed/dialed/received	
Audio Conferencing	Supports 6-way audio conferencing for easy conference calls	
Network Safety	 Physical: Ethernet, dual bridged port for PC bypass IP Mode: IPv4/IPv6 IP Configuration: Static IP / DHCP / PPPoE Network Access Control: 802.1x VPN: L2TP / OpenVPN VLAN LLDP QoS RTCP-XR (RFC3611), VQ-RTCPXR (RFC6035) 	
Auto-provision	Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069	
Audio Codec	 Narrowband Codec: G.711a/u, G.723.1, G.726, G.729A/B, iLBC/Opus Wideband Codec: G.722, Opus 	
Power	 DC Power Input: 5V/0.6A Power Consumption(Adapter): 0.8~1.29W Power Consumption(PoE): 1.25~1.86W 	



FIBERME Communications LLC 1749 Old Meadow Rd., Suite 401 McLean, VA 22102, USA

www.fiberme.com

sales@fiberme.com



Copyright © FIBERME[™] Communications LLC. All rights reserved. No parts of this publication may be reproduced or transmit- ted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of FIBERME Communications LLC.